

FROM INSPIRATION TO DESIGN

HEATHER JONES



MIAMISBURG QUILT

Finished size: 15" x 20"

Please be sure to read all of the instructions before getting started. All seam allowances are $\frac{1}{4}$ ".

Fabric requirements:

- Fabric 1: $\frac{3}{8}$ yard (Kona Cotton in Graphite)
- Fabric 2: $\frac{1}{4}$ yard (Kona Cotton in Wasabi)
- Fabric 3: $\frac{1}{8}$ yard (Kona Cotton in Shadow)
- Backing Fabric: $\frac{5}{8}$ yard (Kona Cotton in Graphite)
- Binding Fabric: $\frac{1}{4}$ yard (Kona Cotton in Graphite)
- 19" x 24" piece of batting or craft sized package

Note: Fabrics 1, 2, and 3 could also be Fat Quarters

CUTTING INSTRUCTIONS:

Tip: As you cut out the fabric for the pattern, keep all pattern pieces organized by labeling each stack with masking tape marked with the appropriate pattern piece name.

- From Fabric 1, cut (1) $11\frac{1}{2}$ " x Width of Fabric (WOF) strip. Subcut the strip into (1) $4\frac{1}{2}$ " x $11\frac{1}{2}$ " rectangle for piece A, (2) $6\frac{1}{2}$ " x $11\frac{1}{2}$ " rectangles for (2) B pieces, and (1) $1\frac{1}{2}$ " x $11\frac{1}{2}$ " strip for piece C.
- From the remaining Fabric 1 from Step 1, cut (1) $2\frac{1}{2}$ " x $4\frac{1}{2}$ " for (1) E piece, and (2) $3\frac{1}{2}$ " x $4\frac{1}{2}$ " for (2) G pieces.
- From Fabric 2, cut (1) $4\frac{1}{2}$ " x WOF strip. Subcut the strip into (3) $4\frac{1}{2}$ " x $4\frac{1}{2}$ " squares for a total of (3) F pieces.
- From Fabric 3, cut (1) $1\frac{1}{2}$ " x WOF strip. Subcut the strip into (3) $1\frac{1}{2}$ " x $11\frac{1}{2}$ " strips for (3) D pieces.
- From the backing fabric cut a 20" x 25" piece for the back of the quilt.
- From the binding fabric, cut (2) $2\frac{1}{2}$ " x WOF strips and remove the selvages.

Note: if using a FQ for Fabric 1, cut the FQ into (1) $11\frac{1}{2}$ " x 22" piece and (1) $6\frac{1}{2}$ " x 22" piece. Cut pieces A, (2) B, and C from the $11\frac{1}{2}$ " section; cut E and (2) G from the $6\frac{1}{2}$ " piece.



FROM INSPIRATION TO DESIGN

HEATHER JONES



CONSTRUCT THE QUILT TOP

7. Following the diagram, pin and sew piece E to one piece F. Pin and sew one G piece to the pieced section. Pin and sew another F piece to the pieced section. Pin and sew the other G piece to the pieced section. Pin and sew the last F piece to the pieced section to complete Column 1. Press all seams to the side, towards the F pieces.
8. Following the diagram, pin and sew the A piece to one D piece. Pin and sew one B piece to the pieced section. Pin and sew another D piece to the pieced section. Pin and sew the last B piece to the pieced section. Pin and sew the last D piece to the pieced section. Pin and sew piece C to the pieced section to complete Column 2. Press all seams to the side towards the D pieces.
9. Following the diagram, pin and sew Column 1 to Column 2, right sides together. Press seam open to finish the quilt top.

FINISH THE QUILT

10. Layer the quilt top, batting, and quilt back to make a quilt sandwich. Baste together with pins or basting stitches.
11. Quilt as desired. Trim off any excess batting and fabric after quilting, and square up all sides of the quilt if necessary.
12. Sew the binding strips from Step 6 together to create one continuous length of binding. Bind the quilt as desired.

SUPPORTING LINKS

<http://www.heatherjonesstudio.com/>

SUPPORTED BY:

brother
at your side

